

### Note!

Before installing this product, check the contents of the kit. If anything is missing, please contact an Öhlins dealer.

#### **Kit Contents**

Description	Part No	Pcs
Shock absorber	HO 910	2
Tool preload adjuster	03199-03	1
Sticker set Öhlins	10207-01	1
Owner's manual	07241-02	1

### Note!

Please note that this image is a general representation of the product and may differ slightly from your product.

#### Note!

Please note that during storage and transportation, especially at high ambient temperature, some of the oil and grease used for assembling may leak and stain the packaging. This is in no way detrimental to the product, wipe off the excessive oil/grease with a cloth.

#### **▲ Warning!**

Before installing this product, read the Öhlins Owner's Manual. The shock absorber/front fork/steering damper is an important part of your vehicle and will affect the stability.

## Shock Absorber for Honda CB 1100-2016

HO 910

# **Mounting Instructions**



# **MOUNTING INSTRUCTIONS**

## **▲ Warning!**

It is advisable to have an Öhlins dealer install the shock absorber.

## A Warning!

If working on a raised vehicle, ensure it is securely supported so that it will not tip.

## Note!

Before mounting this product clean the vehicle thoroughly.

## Note!

When working on this product, always see the Vehicle Service Manual for vehicle specific procedures and important data.

1

Put the motorcycle on a workstand so that the rear wheel barely touches the ground.

2

Remove the original shock absorbers.

3

Install the Öhlins shock absorbers by tightening the upper and lower mounting bolts at a torque value as specified in the vehicle service manual.

### Note!


Lower the vehicle so that the suspension is slightly compressed before tightening the screws.

## Caution!


Ensure that all screws are tightened to the correct torque and that nothing fouls or restricts movement of the shock absorber/front fork/steering damper when the suspension is fully compressed or extended. This page intentionally left blank

# ADJUSTMENTS A Warning!

Before riding, always make sure that the basic settings made by Öhlins are according to recommended Setup Data. Read about adjustments and setting up in the Öhlins Owner's Manual before you make any adjustments. Contact an Öhlins dealer if you have any questions about setting up.



The adjustable end eye/bracket must not be threaded out more than that the groove is fully visible beneath the lock nut. This is maximum length. After adjusting, make sure that the lock nut is tightened (30Nm).



# SETUP DATA

Spring Preload	18 mm.
Rebound adjuster	12 Clicks
12 Spring	
Part No	60480-04
Free spring length	230 mm.
Spring rate	Prog. 20-28
Preload adj.range	[0-24] mm

#### Shock absorber data

Length	360 <sup>+10</sup> / <sub>0</sub> mm.
Stroke	93 mm.

Ohlins products are subject to continuous improvement and development, therefore, although these instructions include the most up-to-date information available at the time of printing, minor updates may occur.

© Öhlins Asia Co. Ltd. All rights reserved. Any reprinting or 700/937 unauthorized use without the written Amphur P permission of Öhlins Racing AB is prohibited.

To find the latest information contact an Öhlins distributor. Please contact Öhlins if you have any questions regarding the contents in this document.

N/mm

Part no. MI\_HO 910\_EN\_0 Issued 2019-05-22

Öhlins Asia Co. Ltd 700/937 Moo5, Tambol Nongkhaga, Amphur Phantong, Chonburi Province 20160 Thailand



## www.ohlins.com